

Pebbled ClimaPlus



Features and • Economical, medium textured ceiling Benefits

CLIMAPLUS[™] 15-year Lifetime System Warranty to withstand conditions up to 104 °F (40°C)/ 90% relative humidity without visible sag when used with USG's Donn® Brand Suspension Systems.

panel has upscale appearance.

Applications

- Schools
- Corridors
- General offices
- · Retail stores

Pebbled CLIMAPLUS™ Panels/Donn Brand DX®/DXL™ Suspension System

Acoustical Ceilings

$\begin{array}{c} \textbf{Pebbled} \\ \textbf{\textit{ClimaPlus}}^{\text{\tiny{m}}} \end{array}$

Technical Service 800 USG.4YOU Web Site www.usg.com Samples/Literature 888 874.2450 Samples/Literature Fax 888 874.2348 Customer Service 800 950.3839 Literature Number SC1836

CLIMAPLUS*						(N) UL C	lassified							
Non-Sag Warranty	Edge	Pan	el Size	Class	Item No.	o. NRC	CAC Min.	LR1	Color			Grid Options	Recycled Content ²	
Pebbled <i>ClimaPlus</i> ™Panels	(SQ)	2'x2'x5/8"		Class A	4801	.55	35	.87		White		A, B, C	30%	\$
		2'x4'x5/8" 2'x2'x5/8" 2'x2'x5/8"		Class A	4800	.55	35 35 35	.87	White			A, B	30%	\$
	(SLT)			Class A 480	4805	.55								
	(FLB)			Class A	4867					White		E, F, G	30%	\$
	A Donn® DX®/ DXL™		B Donn DXW™	C CENTRICITE	E TM DO	DNN DX/DXL	E CENTRICITEE		Fineline® 1/8		G FINELINE			
Grid Profile Options														

ASTM E1264 classification Type III, Form 2, Pattern CE ASTM E84 surface burning characteristics

Class A Flame spread: 25 Smoke developed: 10 Weight 0.72 lb./ft.² Thermal resistance R-1.4 Maximum backloading See Warranty for details. Maintenance

Can be cleaned easily with a soft brush or vacuum.

Footnotes

 LR values are shown as averages.
 For details, see the Recycled Content selector. SAFETY FIRST!

Follow good safety practices. Read material safety data sheets and related literature on products before specification and/or installation.

